

### CLD-65D Dynamic Dimmable Circular CFL Kit



#### Features:

- **Smooth dynamic dimming from 10% - 100% without flicker and/or lamp extinction**
- **Advanced design achieving best performance and top reliability**
- **Totally interchangeable with GE 2D 55W tubes extends its application**
- **Up to 75% saving on energy cost with long life for changing bulb much less frequently**
- **UL approval & Energy Star listed**
- **Best lighting sources for Torchiere, table lamp & ceiling lamp systems**
- **Whole kit including compact fluorescent tube, dimming electronic ballast & dimmer switch for easiest handling.**

#### CLD-65D Specifications

System efficacy	68 LPW
Input voltage	120V, 60Hz
Working voltage range	108 - 132 V
Input power	67 W
Lamp current	0.6 A
Operating Frequency	>40kHz
Colour Rendering Index	≥ 82
Ballast Factor	0.95
Min Starting Temp.	- 10 °C
Operating Temp.	< 70 °C
EMI	FCC Class B
Lamp Crest Factor (C.F.)	1.5
Transit protection	OK
Lamp Start, preheat	0.70 S
Dimensions (Ballast)	L: 94mm W: 94mm H: 43mm

#### Ideal for:

**Hotel/Motel**  
**Office**  
**Property Management**  
**Residential use**

- *Lamp life defined according to international standard*



ISO9002

