

EnergyMaster LED Dimmable 5"/6" Interchangeable Recessed Retrofit Kit



Super longer life time



High Lumen Output




Features:


- "Everything in one box" with integrated trim & medium base adaptor for tool-free direct replacement of existing 5" and 6" 120V AC standard recessed can fixture (GU24 socket cable optional).
- Instant-on with full brightness and diffused lens provide smooth & comfortable lumen distribution
- Effective to 10% flicker-free dimming achieves great energy saving while meeting light needs as desired.
- Durable die casting construction and suitable for indoor & wet locations
- Lasts more than 20 times longer than incandescent lamps

Easy to install


Compatible with 5" and 6" standard, flexible mounting with torsion springs




Step 1



Step 2



Step 3



Step 4



| | |
|---------------|--------------------|
| 13W: 800lm | 75W(BR30): 750lm |
| 18W: 1100lm | 120W(BR40): 1150lm |
| Last 36 years | Last 22 months |

Ideal for:

Hotel/Motel Restaurants Property Management
 Healthcare Office Retails/Show Room Residential

| Type | Input Voltage | Nominal Watt(W) | Luminous Flux(Lm) | Rendering index(Ra) | Color Temp.(K) | Rated Ave. life(h) | Lamp Base | Diameter (mm) | Min. Compartment height required |
|---------------|---------------|-----------------|-------------------|---------------------|----------------|--------------------|------------|---------------|----------------------------------|
| LR5/6I-13D830 | 120V | 13 | 800 | ≥ 81 | 3000K | 40,000 | E26, GU24* | 7½": 190 | 4⅓" / 110mm |
| LR5/6I-18D830 | 120V | 18 | 1100 | ≥ 81 | 3000K | 50,000 | E26, GU24* | 7½": 190 | 4⅓" / 110mm |



LM79 LM80 lighting facts

ISO9001:2008 ISO14001:2004 OHSAS 18001:1999